

Multi zone inverter mini split

MODEL: TM12HFDI

TOSOT

Job Name:

Engineer Name:

System No:

Location:

Contractor:

Date:

- File Resubmit
 Approval Other

General Features

- 2 Thermistor control
- 24-Hour on/off Timer
- Auto operation
- Auto restart
- Chaos swing
- Control lock function
- Drain Pump
- Inverter
- High And Low Pressure Protection Features
- Over Load Protection Features
- Over-Current Protection
- Anti Freeze Protection
- Wired controller
- Optional Wireless Remote control



Unit Performance:

Nominal Cooling Capacity (Btu/h)	11,900
Nominal Heating Capacity (Btu/h)	13,100

Piping

Liquid Line (in, OD)	1/4
Gas Line (in, OD)	3/8
Drain OD, ID (in)	1.57

Fan

Type	Centrifugal
Quantity	2
Motor/Drive	Direct Drive
Air Flow Rate (CFM)	324/235/176

Set Temperature

Cooling (°F WB)	61~86
Heating (°F DB)	61~86


Electrical Specification

Power Supply	208-230V / 60Hz
Communications Wire Size	AWG 14/4
Rated Amps (A)	0.35

Unit Specification

Refrigerant Type	R410A
Refrigerant Control	EEV
Sound Pressure (dB(A))	39/35/32
Primary Filter	Yes
Net Weight (lbs)	50.7
Dehumidification (Pt/h)	2.96






Multi zone inverter mini split

MODEL: TM12HFDI

TOSOT

Outline Dimension Diagram



	mm	Inch
A	742	29 7/32
B	491	19 21/64
C	662	26 1/16
D	620	24 13/32
E	700	27 9/16
F	615	24 7/32
G	782	30 25/32
H	156	6 9/64
I	200	4 7/8
J	635	25

GLOSSARY

SEER - Seasonal Energy Efficiency Ratio

EER - Energy Efficiency Ratio

HSPF - Heating Seasonal Performance Factor

MOP - Maximum Overcurrent Protection

MCA - Minimum Circuit Ampacity

TOSOT

5965 Chemin de la Côte de Liesse
Saint laurent, QC, Canada, H4T 1C3

Contact: +1 438 792 1956

info@tosotusa.com

www.tosotusa.com